

A	B	C	D	E	F
0	8.0	8.0	12.0	23.0	28.0
45	9.0	19.5	13.0	12.7	52.0
50	9.0	20.0	14.0	11.7	54.0
60	9.0	20.5	18.0	10.4	59.0
70	9.0	20.0	19.0	9.6	59.0
80	9.0	19.5	24.0	9.1	63.0
90	9.0	18.0	24.0	9.0	60.0

- A. PARKING ANGLE (DEGREES)
- B. STALL WIDTH (FEET)
- C. STALL TO CURB (FEET)
- D. AISLE WIDTH (FEET)
- E. CURB LENGTH (FEET)
- F. MIN. OVERALL DOUBLE ROW WITH AISLE BETWEEN (FEET)



NOTES:

- 1) ALL PARKING SPACE STRIPING TO BE WHITE IN COLOR.
- 2) IF A PARKING LOT SERVES A USE WHICH GENERATES 2,500 OR MORE VEHICLE TRIPS A DAY, SUCH PARKING SPACES SHALL BE MARKED BY WHITE THERMOPLASTIC LINES.
- 3) ALL CITY OF CLEARWATER PROJECTS SHALL BE IN THERMOPLASTIC.

STANDARD PARKING STALL

CITY INDEX NO. 120; 1 OF 1

N.T.S.

CITY OF CLEARWATER, FLORIDA ENGINEERING DEPARTMENT				
				DRAWN BY E.A. STANDARD PARKING STALL DATE 01/09
△	12/09	CHANGED NOTE NO. 2	TRAF. ENG.	CHECKED BY M.Q. INDEX NO. 120
REV.	DATE	DESCRIPTION	APP.	DESIGNED BY B.E. 1 OF 1